



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 126.67x2.62 - NBR - Nitrile - 90 Shore A - Black - ORS4669

<https://www.o-ring-stocks.eu/o-ring-126.67x2.62-nbr-nitrile-90-shore-a-black-ors4669>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 4669                     |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 90 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Color         | Black                    |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                                     |
|-------------------|---------------------------------------------------------------------|
| Alternative names | Nitrile Rubber - NBR                                                |
| Chemical Name     | Acrylonitrile butadiene rubber                                      |
| Description 2     | O-ring NBR - Nitrile 126.67x2.62                                    |
| Material          | NBR - Nitrile                                                       |
| Packaging Unit    | O-ring                                                              |
| Product name      | O-ring 126.67x2.62 Nitrile NBR                                      |
| Size in text      | one hundred and twenty six comma sixty seven by two comma sixty two |
| Trade names       | Lanxess - Zeon - and LG Chem                                        |

### Alternative Size

|                     |               |
|---------------------|---------------|
| AS568 Size Chart    | AS 159        |
| DIN 3771 Size Chart | 126.67x2.62   |
| SMS 1586 Size chart | 126.67 X 2.62 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 2.62 mm    |
| Hardness            | 90 Shore A |
| ID (inner diameter) | 126.67 mm  |
| Temperature Max     | 135 °C     |
| Temperature Min     | -30 °C     |