



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 123.2x6.99 - FFKM - FFPM - 60 Shore A - Black - ORS88501

<https://www.o-ring-stocks.eu/o-ring-123.2x6.99-ffkm-ffpm-60-shore-a-black-ors88501>

### Specificaties

|               |                                     |
|---------------|-------------------------------------|
| Productnummer | 88501                               |
| Merk          | Eurolast                            |
| Categorie     | FFKM O-Rings - 60 Shore A - F606Z94 |
| Materiaal     | FFKM - FFPM                         |
| Kleur         | Zwart                               |
| Color         | Black                               |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| Alternative names | FFPM – Dupont Kalrez                                               |
| Chemical Name     | Perfluoroelastomer                                                 |
| Description 2     | O-ring FFKM - FFPM 123.2x6.99                                      |
| Material          | FFKM - FFPM                                                        |
| Packaging Unit    | O-ring                                                             |
| Product name      | O-ring 123.2x6.99 FFKM                                             |
| Size in text      | one hundred and twenty three comma twenty by six comma ninety nine |

Trade names Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

### Alternative Size

|                     |              |
|---------------------|--------------|
| AS568 Size Chart    | AS 019       |
| DIN 3771 Size Chart | 123.2x6.99   |
| SMS 1586 Size chart | 123.2 X 6.99 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 6.99 mm    |
| Hardness            | 60 Shore A |
| ID (inner diameter) | 123.2 mm   |
| Temperature Max     | 270 °C     |
| Temperature Min     | -25 °C     |