



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 318x2 - FEP-FKM - FDA - ORS173175

<https://www.o-ring-stocks.eu/o-ring-318x2-fep-fkm-fda-ors173175>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 173175                           |
| Merk          | Eurolast                         |
| Categorie     | FEP Encapsulated - Viton O-Rings |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Zwart                            |
| Color         | Black                            |

### Core Spec's

|          |     |
|----------|-----|
| Approval | FDA |
|----------|-----|

|                   |                                             |
|-------------------|---------------------------------------------|
| Alternative names | Viton® - FKM                                |
| Chemical Name     | Fluorocarbon Rubber                         |
| Description 2     | O-ring FKM - FPM - Viton 318x2              |
| Material          | FKM - FPM - Viton                           |
| Packaging Unit    | O-ring                                      |
| Product name      | O-ring 318x2 FKM - FPM - Viton              |
| Size in text      | three hundred and eighteen zero by two zero |
| Trade names       | Viton® - Du Pont - 3M - Solvay - Daikin     |

### Alternative Size

|                     |       |
|---------------------|-------|
| DIN 3771 Size Chart | 318x2 |
| ISO 3601 Size Chart | 318x2 |
| SMS 1586 Size chart | 318x2 |

### Core Spec's

|                             |        |
|-----------------------------|--------|
| CS (Cross Section)          | 2 mm   |
| ID (inner diameter)         | 318 mm |
| Temperature Max             | 205 °C |
| Temperature Min             | -20 °C |
| Tolerance (CS) DIN 7715-M2F | ± 0,12 |
| Tolerance (ID) DIN 7715-M2F | N/A    |