



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 67x3 - FEP-FKM - FDA - ORS152956

<https://www.o-ring-stocks.eu/o-ring-67x3-fep-fkm-fda-ors152956>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 152956                           |
| Merk          | Eurolast                         |
| Categorie     | FEP Encapsulated - Viton O-Rings |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Zwart                            |
| Color         | Black                            |

### Core Spec's

|          |     |
|----------|-----|
| Approval | FDA |
|----------|-----|

|                   |                                |
|-------------------|--------------------------------|
| Alternative names | Viton® - FKM                   |
| Chemical Name     | Fluorocarbon Rubber            |
| Description 2     | O-ring FKM - FPM - Viton 67x3  |
| Material          | FKM - FPM - Viton              |
| Packaging Unit    | O-ring                         |
| Product name      | O-ring 67x3 FKM - FPM - Viton  |
| Size in text      | sixty seven zero by three zero |
| Trade names       | Teflex FEP-O-SEAL®             |

### Alternative Size

|                     |      |
|---------------------|------|
| DIN 3771 Size Chart | 67x3 |
| ISO 3601 Size Chart | 67x3 |
| SMS 1586 Size chart | 67x3 |

### Core Spec's

|                             |        |
|-----------------------------|--------|
| CS (Cross Section)          | 3 mm   |
| ID (inner diameter)         | 67 mm  |
| Temperature Max             | 205 °C |
| Temperature Min             | -20 °C |
| Tolerance (CS) DIN 7715-M2F | ± 0,15 |
| Tolerance (ID) DIN 7715-M2F | ± 0,40 |