



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 70x3.5 - FEP-FKM - FPM - Viton - FDA - ORS112520

<https://www.o-ring-stocks.eu/o-ring-70x3.5-fep-fkm-fpm-viton-fda-ors112520>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 6521553                          |
| Merk          | Eurolast                         |
| Categorie     | FEP Encapsulated - Viton O-Rings |
| Materiaal     | FEP-FKM - FPM - Viton            |
| Kleur         | Zwart                            |
| Color         | Black                            |

### Core Spec's

|          |     |
|----------|-----|
| Approval | FDA |
|----------|-----|

|                   |                                                    |
|-------------------|----------------------------------------------------|
| Alternative names | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM |
| Chemical Name     | Teflon® fluoropolymer - Viton                      |
| Description 2     | O-ring FEP-FKM - FPM - Viton 70x3.5                |
| Material          | FEP-FKM - FPM - Viton                              |
| Packaging Unit    | O-ring                                             |
| Product name      | O-ring 70x3.5 FEP-FPM - Viton                      |
| Size in text      | seventy zero by three comma fifty                  |
| Trade names       | Teflex FEP-O-SEAL®                                 |

### Alternative Size

|                     |          |
|---------------------|----------|
| DIN 3771 Size Chart | 70x3.5   |
| SMS 1586 Size chart | 70 X 3.5 |

### Core Spec's

|                             |        |
|-----------------------------|--------|
| CS (Cross Section)          | 3.5 mm |
| ID (inner diameter)         | 70 mm  |
| Temperature Max             | 205 °C |
| Tolerance (CS) DIN 7715-M2F | ± 0,15 |
| Tolerance (ID) DIN 7715-M2F | ± 0,50 |