



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 29.51x5.33 - FEP-FKM - FPM - Viton - FDA - ORS112400

<https://www.o-ring-stocks.eu/o-ring-29.51x5.33-fep-fkm-fpm-viton-fda-ors112400>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 6521426                          |
| Merk          | Eurolast                         |
| Categorie     | FEP Encapsulated - Viton O-Rings |
| Materiaal     | FEP-FKM - FPM - Viton            |
| Kleur         | Zwart                            |
| Color         | Black                            |

### Core Spec's

|          |     |
|----------|-----|
| Approval | FDA |
|----------|-----|

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Alternative names | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM     |
| Chemical Name     | Teflon® fluoropolymer - Viton                          |
| Description 2     | O-ring FEP-FKM - FPM - Viton 29.51x5.33                |
| Material          | FEP-FKM - FPM - Viton                                  |
| Packaging Unit    | O-ring                                                 |
| Product name      | O-ring 29.51x5.33 FEP-FPM - Viton                      |
| Size in text      | twenty nine comma fifty one by five comma thirty three |
| Trade names       | Teflex FEP-O-SEAL®                                     |

### Alternative Size

|                     |              |
|---------------------|--------------|
| AS568 Size Chart    | AS 023       |
| DIN 3771 Size Chart | 29.51x5.33   |
| SMS 1586 Size chart | 29.51 X 5.33 |

### Core Spec's

|                             |          |
|-----------------------------|----------|
| CS (Cross Section)          | 5.33 mm  |
| ID (inner diameter)         | 29.51 mm |
| Temperature Max             | 205 °C   |
| Tolerance (CS) DIN 7715-M2F | ± 0,12   |
| Tolerance (ID) DIN 7715-M2F | ± 0,925  |