



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 16x3 - FEP-VMQ - MVQ - Silicone - FDA - ORS113136

<https://www.o-ring-stocks.eu/o-ring-16x3-fep-vmq-mvq-silicone-fda-ors113136>

### Specificaties

|               |                                     |
|---------------|-------------------------------------|
| Productnummer | 6522209                             |
| Merk          | Eurolast                            |
| Categorie     | FEP Encapsulated - Silicone O-Rings |
| Materiaal     | FEP-VMQ - MVQ - Silicone            |
| Kleur         | Rood                                |
| Color         | Red                                 |

### Core Spec's

|          |     |
|----------|-----|
| Approval | FDA |
|----------|-----|

|                   |                                                                             |
|-------------------|-----------------------------------------------------------------------------|
| Alternative names | FEP-VMQ / VMQ - FEP Encapsulated / FEP-Silicone / Silicone FEP Encapsulated |
| Chemical Name     | Teflon® fluoropolymer - Silicone                                            |
| Description 2     | O-ring FEP-VMQ - MVQ - Silicone 16x3                                        |
| Material          | FEP-VMQ - MVQ - Silicone                                                    |
| Packaging Unit    | O-ring                                                                      |
| Product name      | O-ring 16x3 FEP-VMQ - Silicone                                              |
| Size in text      | sixteen zero by three zero                                                  |
| Trade names       | Teflex FEP-O-SEAL®                                                          |

### Alternative Size

|                     |        |
|---------------------|--------|
| AS568 Size Chart    | AS 040 |
| DIN 3771 Size Chart | 16x3   |
| SMS 1586 Size chart | 16 X 3 |

### Core Spec's

|                             |           |
|-----------------------------|-----------|
| CS (Cross Section)          | 3 mm      |
| ID (inner diameter)         | 16 mm     |
| Temperature Max             | 205 °C    |
| Tolerance (CS) DIN 7715-M2F | ± 0,15 mm |
| Tolerance (ID) DIN 7715-M2F | ± 0,40 mm |