



O-ring-Stocks.eu - Techniparts

Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 40.64x5.34 - EDPM - Sulfer - 70 Shore A - Black - ORS159437

<https://www.o-ring-stocks.eu/o-ring-40.64x5.34-edpm-sulfer-70-shore-a-black-ors159437>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 159437                    |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | ZWART                     |
| Color         | Black                     |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                |                                                  |
|----------------|--------------------------------------------------|
| Chemical Name  | Ethylene propylene diene monomer                 |
| Description 2  | O-ring EPDM 40.64x5.34                           |
| Material       | EPDM                                             |
| Packaging Unit | O-ring                                           |
| Product name   | O-ring 40.64x5.34 EPDM                           |
| Size in text   | forty comma sixty four by five comma thirty four |
| Trade names    | Dow Chemical - ExxonMobil - and Lion Elastomers  |

### Alternative Size

|                     |            |
|---------------------|------------|
| DIN 3771 Size Chart | 40.64x5.34 |
| ISO 3601 Size Chart | 40.64x5.34 |
| SMS 1586 Size chart | 40.64x5.34 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 5.34 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 40.64 mm   |
| Temperature Max     | 125 °C     |
| Temperature Min     | -40 °C     |
| Vulcanisation       | Sulfur     |