



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 59x3.5 - VMQ - MVQ - Silicone - FDA - EC1935/2004 - 70 Shore A -

<https://www.o-ring-stocks.eu/o-ring-59x3.5-vmq-mvq-silicone-fda-ec19352004-70-shore-a-red-ors135290>

### Specificaties

|               |                                                         |
|---------------|---------------------------------------------------------|
| Productnummer | 135290                                                  |
| Merk          | Eurolast                                                |
| Categorie     | VMQ - MVQ - Silicone - O-Rings - 70 Shore A - Red - FDA |
| Materiaal     | VMQ - MVQ - Silicone                                    |
| Kleur         | ROOD                                                    |
| Color         | Red                                                     |

### Core Spec's

|          |                                   |
|----------|-----------------------------------|
| Approval | FDA 21 CFR 177.2600 – EC1935/2004 |
|----------|-----------------------------------|

|                   |                                               |
|-------------------|-----------------------------------------------|
| Alternative names | Silicone Rubber - PVMQ                        |
| Chemical Name     | Vinyl Methyl Silicone                         |
| Description 2     | O-ring VMQ - MVQ - Silicone 59x3.5            |
| Material          | Silicone - VMQ - MVQ                          |
| Packaging Unit    | O-ring                                        |
| Product name      | O-ring 59x3.5 VMQ - MVQ - Silicone            |
| Size in text      | fifty nine zero by three comma fifty          |
| Trade names       | Eriks - Wacker - Eastern Seals - and BlueStar |

### Alternative Size

|                     |        |
|---------------------|--------|
| DIN 3771 Size Chart | 59x3.5 |
| ISO 3601 Size Chart | 59x3.5 |
| SMS 1586 Size chart | 59x3.5 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 3.5 mm     |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 59 mm      |
| Temperature Max     | 210 °C     |
| Temperature Min     | -50 °C     |