



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 215.27x5.33 - EDPM - Sulfer - 70 Shore A - Black - ORS11862

<https://www.o-ring-stocks.eu/o-ring-215.27x5.33-edpm-sulfer-70-shore-a-black-ors11862>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 11862                     |
| EAN           | 6150547064080             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Color         | Black                     |

### Core Spec's

|                |                                                                       |
|----------------|-----------------------------------------------------------------------|
| Approval       | None                                                                  |
| Chemical Name  | Ethylene propylene diene monomer                                      |
| Description 2  | O-ring EPDM 215.27x5.33                                               |
| Material       | EPDM                                                                  |
| Packaging Unit | O-ring                                                                |
| Product name   | O-ring 215.27x5.33 EPDM                                               |
| Size in text   | two hundred and fifteen comma twenty seven by five comma thirty three |
| Trade names    | Dow Chemical - ExxonMobil - and Lion Elastomers                       |

### Alternative Size

|                     |               |
|---------------------|---------------|
| AS568 Size Chart    | AS 371        |
| DIN 3771 Size Chart | 215.27x5.33   |
| SMS 1586 Size chart | 215.27 X 5.33 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 5.33 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 215.27 mm  |
| Temperature Max     | 125 °C     |
| Temperature Min     | -40 °C     |
| Vulcanisation       | Sulfur     |